



Dongguan Baoxu Chemical Technology, Ltd.

P: +86-0769-22821082 Fax: 0769-22821083

Email: info@baoxuchem.com Web: www.baoxuchem.com

Room 1118 Caijin Business Building Nancheng District Guangdong

ANTIOXIDANT BHT/264


Chemical name:

2,6 di-tert-butyl-4-methylphenol

Formula $C_{15}H_{24}O$

Molecular Weight 220.36

CAS# 128-37-0



Specification:

Item	Items
Content, % \geq	99.9
Chromaticity (Pt-Co), number \leq	30
Melting point (initial melting) / $^{\circ}C \geq$	69.0
Moisture, w/% \leq	0.05
Burning residue, w /% \leq	0.005
Sulfate (calculated as SO_4), w /% \leq	0.002
Arsenic (As) / (mg / kg) \leq	1
Heavy metal (in Pb) / (mg / kg) \leq	5
Free phenol (based on p-cresol), w /% \leq	0.02

Application: > BHT is suitable for all kinds of animal, vegetable oil products and other kinds of grain and oil foods, snack foods, food packaging materials, food grade plastic products.

Widely used in all kinds of cosmetics, all kinds of sporting goods, and replace industrial-grade antioxidants (T501) widely used in industrial and engineering plastic products, PU paste, polyether, high-grade paints and coatings, anti-corrosion materials, etc.; also for lubricating oil, secondary processing gasoline, paraffin, mineral oil, polypropylene, polyethylene, polystyrene, ABS resin, polyester, cellulose resin, foam stabilizers antioxidant. It is non-polluting antioxidant stabilizers for natural rubber, butadiene rubber, styrene butadiene rubber, neoprene rubber, nitrile rubber, butyl rubber, isoprene rubber, ethylene propylene rubber, transformer oil, various types of latex products (especially white or light rubber products, latex).

The information and statement herein are believed to be reliable but are not to be construed as a warranty or representation for which we assume legal responsibility, Users should undertake sufficient verification and testing to determine the suitable for their own particular purpose of any information or products referred to herein. No warranty of fitness for a particular purpose is made.



Dongguan Baoxu Chemical Technology.,Ltd.
P:+86-0769-22821082 Fax:0769-22821083
Email:info@baoxuchem.com Web:www.baoxuchem.com
Room1118 Caijin Business Building Nancheng Distinct Guangdong

Package: This product is lined with food-grade plastic film bag, white multi-layer kraft paper woven composite bag, and covered with plastic film (waterproof, moisture-proof) packaging, 25kg / bag. This product should be stored in a special indoor warehouse that is dry and protected from light, and must be placed under the cushion to prevent moisture (see the back side of the package for details). When transporting and unloading this product, prevent rain; avoid direct sunlight; ensure that the drying and packaging bags are not damaged or contaminated by other items. This product must not be mixed with or mixed with toxic or hazardous materials during storage and transportation. The storage period of this product is 2 years

The information and statement herein are believed to be reliable but are not to be construed as a warranty or representation for which we assume legal responsibility, Users should undertake sufficient verification and testing to determine the suitability for their own particular purpose of any information or products referred to herein. No warranty of fitness for a particular purpose is made.