



Dongguan Baoxu Chemical Technology, Ltd.

P:+86-0769-22821082 Fax:0769-22821083

Email:info@additivesforpolymer.com Web:www.additivesforpolymer.com

8th Chenwu East Road, Houjie Town, Dongguan City, Guangdong Province, China

4-tert-butylcatechol 85% Solution

Description

Product Name :4-tert-butylcatechol, 4-tert-Butylpyrocatechol, TBC Solvay

Equivalent Name: TBC OPTIMA 85% Flakes

Cas No. : 98-29-3

Application

4-tert-butylcatechol Solution is mainly used as an efficient polymerization inhibitor during the processing or storage and transportation of olefin monomer; Used as an antioxidant for polymer materials and oils.

Typical Properties

Test item	Standard value
Appearance	light yellow to amber colored liquid
TBK content	≥85
Water content	≤15
Density	1.05-1.07
Reflection rate	1.5-1.512

Packing

Liquid products are packed in plastic barrels, with a net weight of 20kg per barrel; Solid products are packed in carton barrels (lined with plastic bags), with a net weight of 25kg per barrel; It can also be packaged according to user requirements.

The information and statement herein are believed to be reliable but are not to be construed as a warranty or representation for which we assume legal responsibility, Users should undertake sufficient verification and testing to determine the suitability for their own particular purpose of any information or products referred to herein. No warranty of fitness for a particular purpose is made.



Dongguan Baoxu Chemical Technology.,Ltd.

P:+86-0769-22821082 Fax:0769-22821083

Email:info@additivesforpolymer.com Web:www.additivesforpolymer.com

8th Chenwu East Road, Houjie Town, Dongguan City, Guangdong Province, China

Avoid excessive heating or direct sunlight during transportation, and should also comply with GB/T191 regulations. When storing, it must be sealed, isolated from air, and placed in a cool and dry room, and it is forbidden to contact with alkalis, iron, and copper to avoid oxidation.

Product Form

The solid 4-tert-butylcatechol produced by our company, which can use toluene, methanol, styrene, and water as solvents according to user needs, and is configured as a polymerization inhibitor that can be used directly on the device.

The information and statement herein are believed to be reliable but are not to be construed as a warranty or representation for which we assume legal responsibility, Users should undertake sufficient verification and testing to determine the suitable for their own particular purpose of any information or products referred to herein. No warranty of fitness for a particular purpose is made.